



Project Name: _____

Location: _____

Item #: _____ Qty: _____

Model: _____

GLASS DOOR INDOOR WINE COOLER

MODEL: MCWC28



MCWC28


Maxx Ice Indoor wine coolers are ideal for residential and commercial environments. Perfect for any indoor entertainment space, this unit can be free standing or built-in, has a storage capacity of up to 28 bottles and features interior LED lighting.

FEATURES AND CONSTRUCTION

- Exterior finish is available in black painted steel
- Easy to clean, low-maintenance ABS interior
- Energy efficient interior LED lighting - ability to toggle between white and blue light
- 6 curved metallic wire bottle racks, with a storage capacity of 28 total bottles
- Adjustable leveling feet
- Electronic control panel with LCD digital display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Polyurethane foam insulation provides outstanding thermal regulation and energy efficiency
- Approved for residential & commercial applications

ELECTRIC

115V / 60Hz / 1Ph
(230V / 50-60Hz / 1Ph is available as an option)
6' (2m) NEMA 5-15P cord set included



NEMA 5-15P

TEMPERATURE

Holding temperature 35°F to 40°F (1°C to 5°C)

- Digital control system maintains optimum temperature
- This unit is designed to store pre-chilled product at the ideal serving temperature and is not intended to perform as a pull down refrigerator

3RD PARTY APPROVALS



Intertek

Certified to ANSI NSF 12



Intertek

Certified to ANSI UL 563




DOE 2018 Compliant

MAXX ICE WARRANTY (USA / CANADA)


Contact Maxx Ice for warranty statement at
TechnicalServices@TheLegacyCompanies.com or 877.368.2797




FRONT VIEW



SIDE VIEW



TOP VIEW



MODEL	EXTERNAL DIMENSIONS	HOLDING TEMPERATURE RANGE	AMP DRAW	BOTTLE RACKS / BOTTLE CAPACITY	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	ELECTRICAL
MCWC28	14.5" x 23" x 33.5" (368 x 584 x 851 mm)	35°F to 40°F (1°C to 5°C)	2.0A	6 / 28	76 lbs (34 kg)	R-134a 2.3 oz (65.2 g)	115V / 60Hz / 1Ph

INSTALLATION

- A minimum clearance of 1/4" on the sides, 1/2" in the rear and 1" on top is recommended to promote adequate cooling air circulation
- Minimum cutout size for undercounter installation is 15" x 33.75"