

XD551

HOOD-TYPE DISHWASHER



PRODUCT DESCRIPTION

100% STAINLESS STEEL

Structure, body and tank in AISI 304 stainless steel.

Rotating lower and upper wash and rinse arms.

Stainless steel pump suction filter.

Electromechanical operation.

Two working cycles: 60 seconds and 150 seconds.

Stainless steel heating elements, resistant to corrosion and limescale.

Can be installed and operated both in-line and at an angle. Height-adjustable feet.

Spring-loaded hood lifting system.

The operating cycle starts by closing the hood.

Device for interrupting machine operation in the event of accidental opening of the hood during the work cycle.

The rinse aid dispenser comes as standard to ensure excellent drying results.

The detergent dispenser is pre-installed as standard.

The provision for the drain pump is standard.

Stainless steel surface filter available as an option on request.

A plate basket and a cup basket are included.

Maximum ease of use: with just one control button (in addition to the ON/OFF button), the dishwasher is easy to use, even for inexperienced operators.

A perfect solution for premises with high staff turnover.



TECHNICAL SPECIFICATIONS

Width: 660 mm
Depth: 785 mm
Height: 1420 mm
Volume: 0.83 m³
Basket dimensions: 500x500 mm Useful
height: 395 Working
cycles: 2 Electrical
power: 6.80 kW
Power supply: 230 V / 1 - 230 V / 3 - 400 V / 3+N/ 50-60 Hz Dishes/Hour:
1080-432

